

Potter's Choice

Cone 5-6

Layering



PC-60 Layering Notes: Apply two layers of base coat. Apply two layers of top coat. (Let dry between coats.)

Clay: AMACO® Buff Stoneware No. 46
Firing: Test tiles have been fired to Cone 6

www.layeringpcs.info



Join the conversation
www.facebook.com/groups/potterschoiceex

over
PC-60
Salt Buff



Color may vary between printed copies.

PC-35
Oil Spot
over
PC-60
Salt Buff*



PC-42
Seaweed
over
PC-60
Salt Buff*



PC-53
Ancient
Jasper
over
PC-60
Salt Buff*



PC-36
Ironstone
over
PC-60
Salt Buff*



PC-43
Toasted
Sage
over
PC-60
Salt Buff*



PC-57
Smoky
Merlot
over
PC-60
Salt Buff*



PC-37
Smoked
Sienna
over
PC-60
Salt Buff*



PC-49
Frosted
Melon
over
PC-60
Salt Buff*



PC-59
Deep
Firebrick
over
PC-60
Salt Buff*



PC-40
True
Celadon
over
PC-60
Salt Buff*



PC-50
Shino
over
PC-60
Salt Buff*



PC-61
Textured
Amber
over
PC-60
Salt Buff*



The Art & Creative Materials Institute CL (Caution Label) seal restricts this product from children under the age of 13. Older users must follow all cautionary labeling. Conforms to ASTM D-4236.

WARNING (PC-1, PC-32, & PC-60): These products contain a chemical known to the State of California to cause birth defects or other reproductive harm.

PC-52
Deep Sienna
Speckle
over
PC-60
Salt Buff*



PC-62
Textured
Amber Brown
over
PC-60
Salt Buff*



Reorder No. 11698V